



SIERUTA

CB mini - hydraulisk overfaldsskovl til minigraver

Modeller og specifikationer

Model	Maskinklas se [t]	Bredde [mm]	Højde [mm]	Længde [mm]	Volumen SAE [dm ³]	Antal tænder	Spidsradiu s [mm]	Tandsyste mer	Adapter	Beslag til h urtigskifte	D [mm]	E [mm]	Vægt [kg]
CBR-20	1,2-1,8	550	464	462	52	4	322	E701, E11.7	S30	S30 · MS01 · M02 · HS02 · CW05 · Klac C	478	350	65
CBR-30	1,8-2,5	600	448	557	83	4	416	E11.4, V13	S40	S40 · MS03 · M03 · HS02 CW05 · OQ40 · klac C	590	450	80
CBR-40	2,5-4,0	600	547	655	113	4	492	E11.4, V13	S40	S40 · MS03 · M03 · HS03 · CW05 · OQ40 · Klac D	792	500	107
CBR-60	4,0-6,0	600	593	796	156	4	654	E11.4, V13	S40	S40 · MS03 · M03 · HS06 · CW10 · OQ40 · Klac E	915	600	154
CBR-90	6,0-10	800	670	855	245	5	643	E25, J200, V17	S45	S45 · S50 · MS08 · M10 · HS08 · CW10 · OQ45 · Klac F	982	650	202

Tal som trykt i denne families datablad. En streg betyder, at databladet ikke angiver tallet.