

CB mini - hydraulic clamp bucket for mini-excavator

Models and specifications

Model	Machine class [t]	Width [mm]	Height [mm]	Length [mm]	Capacity SAE [dm ³]	Number of teeth	Tip radius [mm]	Tooth systems	Adapter	Quick coupler brackets	D [mm]	E [mm]	Weight [kg]
CBR-20	1.2-1.8	550	464	462	52	4	322	E701, E11.7	S30	S30 · MS01 · M02 · HS02 · CW05 · Klac C	478	350	65
CBR-30	1.8-2.5	600	448	557	83	4	416	E11.4, V13	S40	S40 · MS03 · M03 · HS02 · CW05 · OQ40 · klac C	590	450	80
CBR-40	2.5-4.0	600	547	655	113	4	492	E11.4, V13	S40	S40 · MS03 · M03 · HS03 · CW05 · OQ40 · Klac D	792	500	107
CBR-60	4.0-6.0	600	593	796	156	4	654	E11.4, V13	S40	S40 · MS03 · M03 · HS06 · CW10 · OQ40 · Klac E	915	600	154
CBR-90	6.0-10	800	670	855	245	5	643	E25, J200, V17	S45	S45 · S50 · MS08 · M10 · HS08 · CW10 · OQ45 · Klac F	982	650	202

Figures as printed on this family's datasheet. A dash means the datasheet does not state that figure.