

GB - rigid grading & ditching bucket, German profile

Models and specifications

Model	Machine class [t]	Width [mm]	Height [mm]	Length [mm]	Capacity SAE [dm³]	Tip radius [mm]	Quick coupler brackets	Weight [kg]
GB-10	0.6-1.2	600	237	289	28	238	S30 · MS01 · M02 · CW00	22
GB-10	0.6-1.2	800	237	289	39	238	S30 · MS01 · M02 · CW00	28
GB-10	0.6-1.2	1000	237	289	50	238	S30 · MS01 · M02 · CW00	34
GB-20	1.2-1.8	800	294	357	57	309	S30 · MS01 · M02 · HS02 · CW05 · Klac C	39
GB-20	1.2-1.8	1000	294	357	72	309	S30 · MS01 · M02 · HS02 · CW05 · Klac C	47
GB-20	1.2-1.8	1200	294	357	85	309	S30 · MS01 · M02 · HS02 · CW05 · Klac C	55
GB-30	1.8-2.5	1000	346	407	93	348	S40 · MS03 · M03 · HS02 CW05 · OQ40 · klac C	70
GB-30	1.8-2.5	1200	346	407	114	348	S40 · MS03 · M03 · HS02 CW05 · OQ40 · klac C	82
GB-40	2.5-4.0	1000	390	446	124	400	S40 · MS03 · M03 · HS03 · CW05 · OQ40 · Klac D	81
GB-40	2.5-4.0	1200	390	446	150	400	S40 · MS03 · M03 · HS03 · CW05 · OQ40 · Klac D	94
GB-40	2.5-4.0	1400	390	446	176	400	S40 · MS03 · M03 · HS03 · CW05 · OQ40 · Klac D	107
GB-60	4.0-6.0	1200	442	507	187	445	S40 · MS03 · M03 · HS06 · CW10 · OQ40 · Klac E	111
GB-60	4.0-6.0	1400	442	507	220	445	S40 · MS03 · M03 · HS06 · CW10 · OQ40 · Klac E	127

Figures as printed on this family's datasheet. A dash means the datasheet does not state that figure.

Model	Machine class [t]	Width [mm]	Height [mm]	Length [mm]	Capacity SAE [dm ³]	Tip radius [mm]	Quick coupler brackets	Weight [kg]
GB-60	4.0-6.0	1500	442	507	236	445	S40 · MS03 · M03 · HS06 · CW10 · OQ40 · Klac E	135
GB-60	4.0-6.0	1600	442	507	253	445	S40 · MS03 · M03 · HS06 · CW10 · OQ40 · Klac E	143
GB-90	6.0-10	1500	475	559	275	479	S45 · S50 · MS08 · M10 · HS08 · CW10 · OQ45 · Klac F	170
GB-90	6.0-10	1600	475	559	295	479	S45 · S50 · MS08 · M10 · HS08 · CW10 · OQ45 · Klac F	180
GB-90	6.0-10	1800	475	559	334	479	S45 · S50 · MS08 · M10 · HS08 · CW10 · OQ45 · Klac F	200

Figures as printed on this family's datasheet. A dash means the datasheet does not state that figure.