

GBH - hydraulic tilt ditching bucket for mini-excavator

Models and specifications

Model	Machine class [t]	Width [mm]	Height [mm]	Length [mm]	Capacity SAE [dm³]	Tip radius [mm]	Quick coupler brackets	Weight [kg]
GBH-10	0.6-1.2	800	237	289	39	405	S30 · MS01 · M02 · CW00	57
GBH-10	0.6-1.2	1000	237	289	50	405	S30 · MS01 · M02 · CW00	63
GBH-20	1.2-1.8	800	294	357	57	470	S30 · MS01 · M02 · HS02 · CW05 · Klac C	70
GBH-20	1.2-1.8	1000	294	357	72	470	S30 · MS01 · M02 · HS02 · CW05 · Klac C	78
GBH-20	1.2-1.8	1200	294	357	85	470	S30 · MS01 · M02 · HS02 · CW05 · Klac C	86
GBH-30	1.8-2.5	1000	346	407	93	510	S40 · MS03 · M03 · HS02 CW05 · OQ40 · klac C	101
GBH-30	1.8-2.5	1200	346	407	114	510	S40 · MS03 · M03 · HS02 CW05 · OQ40 · klac C	113
GBH-40	2.5-4.0	1000	390	446	124	587	S40 · MS03 · M03 · HS03 · CW05 · OQ40 · Klac D	128
GBH-40	2.5-4.0	1200	390	446	150	587	S40 · MS03 · M03 · HS03 · CW05 · OQ40 · Klac D	142
GBH-40	2.5-4.0	1400	390	446	176	587	S40 · MS03 · M03 · HS03 · CW05 · OQ40 · Klac D	155
GBH-40	2.5-4.0	1500	390	446	190	587	S40 · MS03 · M03 · HS03 · CW05 · OQ40 · Klac D	162
GBH-60	4.0-6.0	1200	442	507	187	658	S40 · MS03 · M03 · HS06 · CW10 · OQ40 · Klac E	182

Figures as printed on this family's datasheet. A dash means the datasheet does not state that figure.

Model	Machine class [t]	Width [mm]	Height [mm]	Length [mm]	Capacity SAE [dm ³]	Tip radius [mm]	Quick coupler brackets	Weight [kg]
GBH-60	4.0-6.0	1400	442	507	220	658	S40 · MS03 · M03 · HS06 · CW10 · OQ40 · Klac E	198
GBH-60	4.0-6.0	1500	442	507	236	658	S40 · MS03 · M03 · HS06 · CW10 · OQ40 · Klac E	206
GBH-60	4.0-6.0	1600	442	507	253	658	S40 · MS03 · M03 · HS06 · CW10 · OQ40 · Klac E	214
GBH-90	6.0-10	1500	475	559	275	682	S45 · S50 · MS08 · M10 · HS08 · CW10 · OQ45 · Klac F	267
GBH-90	6.0-10	1600	475	559	295	682	S45 · S50 · MS08 · M10 · HS08 · CW10 · OQ45 · Klac F	277
GBH-90	6.0-10	1800	475	559	334	682	S45 · S50 · MS08 · M10 · HS08 · CW10 · OQ45 · Klac F	297

Figures as printed on this family's datasheet. A dash means the datasheet does not state that figure.