

SIERUTA

GD - rigid grading & ditching bucket, 12-40 t

Models and specifications

Model	Machine class [t]	Width [mm]	Height [mm]	Length [mm]	Capacity SAE [dm ³]	Tip radius [mm]	Quick coupler brackets	Weight [kg]
GD-160	12-16	1600	563	807	484	547	S60 · MS10 · OQ60 · OQ65 · M18 · S1 · SW33	305
GD-160	12-16	1800	563	807	550	547	S60 · MS10 · OQ60 · OQ65 · M18 · S1 · SW33	338
GD-160	12-16	2000	563	807	615	547	S60 · MS10 · OQ60 · OQ65 · M18 · S1 · SW33	370
GD-190	16-19	1600	603	865	544	585	S60 · MS10 · OQ65 · M26 · S1 · SW33	325
GD-190	16-19	1800	603	865	618	585	S60 · MS10 · OQ65 · M26 · S1 · SW33	358
GD-190	16-19	2000	603	865	692	585	S60 · MS10 · OQ65 · M26 · S1 · SW33	390
GD-230	19-23	1600	661	937	644	643	S70 · MS21 · OQ65 · OQ70 · M26 · S2 · SW33	365
GD-230	19-23	1800	661	937	731	643	S70 · MS21 · OQ65 · OQ70 · M26 · S2 · SW33	403
GD-230	19-23	2000	661	937	819	643	S70 · MS21 · OQ65 · OQ70 · M26 · S2 · SW33	441
GD-300	23-30	1800	784	1130	1059	768	S70 · MS21 · OQ70 · OQ70-55 · S2 · SW48	691
GD-300	23-30	2000	784	1130	1188	768	S70 · MS21 · OQ70 · OQ70-55 · S2 · SW48	752
GD-300	23-30	2400	784	1130	1447	768	S70 · MS21 · OQ70 · OQ70-55 · S2 · SW48	874
GD-400	30-40	2000	848	1231	1395	827	S80 · MS25 · OQ80 · S3 · SW48	856
GD-400	30-40	2400	848	1231	1700	827	S80 · MS25 · OQ80 · S3 · SW48	988

Figures as printed on this family's datasheet. A dash means the datasheet does not state that figure.

Model	Machine class [t]	Width [mm]	Height [mm]	Length [mm]	Capacity SAE [dm³]	Tip radius [mm]	Quick coupler brackets	Weight [kg]
GD-400	30-40	2600	848	1231	1851	827	S80 · MS25 · OQ80 · S3 · SW48	1055

Figures as printed on this family's datasheet. A dash means the datasheet does not state that figure.