

GPLO - GPL bucket with perforated bottom

Models and specifications

Model	Machine class [t]	Width [mm]	Height [mm]	Length [mm]	Capacity SAE [dm³]	Tip radius [mm]	Tooth systems	Quick coupler brackets	Weight [kg]
GPLO-20	1.2-1.8	600	375	410	59	370	E701, E11.7	S30 · MS01 · M02 · HS02 · CW05	32
GPLO-20	1.2-1.8	800	375	410	70	370	E701, E11.7	S30 · MS01 · M02 · HS02 · CW05	43
GPLO-30	1.8-2.5	600	433	465	79	438	E11.4, V13	S40 · MS03 · M03 · HS02 · CW05 · OQ40	43
GPLO-30	1.8-2.5	800	433	465	110	438	E11.4, V13	S40 · MS03 · M03 · HS02 · CW05 · OQ40	55
GPLO-40	2.5-4.0	600	507	529	103	518	E11.4, V13	S40 · MS03 · M03 · HS03 · CW05 · OQ40	56
GPLO-40	2.5-4.0	800	507	529	145	518	E11.4, V13	S40 · MS03 · M03 · HS03 · CW05 · OQ40	71
GPLO-60	4.0-6.0	600	602	658	150	611	E11.4, V13	S40 · MS03 · M03 · HS06 · CW10 · OQ40	81
GPLO-60	4.0-6.0	800	602	658	211	611	E11.4, V13	S40 · MS03 · M03 · HS06 · CW10 · OQ40	101
GPLO-60	4.0-6.0	1000	602	658	272	611	E11.4, V13	S40 · MS03 · M03 · HS06 · CW10 · OQ40	121
GPLO-75	6.0-7.5	600	667	719	175	667	E25, J200, V17	S40/240 · MS08 · M10 · HS06 · CW10 · OQ45	103
GPLO-75	6.0-7.5	800	667	719	248	667	E25, J200, V17	S40/240 · MS08 · M10 · HS06 · CW10 · OQ45	128
GPLO-75	6.0-7.5	1000	667	719	321	667	E25, J200, V17	S40/240 · MS08 · M10 · HS06 · CW10 · OQ45	152

Figures as printed on this family's datasheet. A dash means the datasheet does not state that figure.

Model	Machine class [t]	Width [mm]	Height [mm]	Length [mm]	Capacity SAE [dm³]	Tip radius [mm]	Tooth systems	Quick coupler brackets	Weight [kg]
GPLO-95	7.5-10	800	717	770	283	716	E25, J200, V17	S45 · S50 · MS08 · M10 · HS08 · CW10 · OQ45	144
GPLO-95	7.5-10	1000	717	770	367	716	E25, J200, V17	S45 · S50 · MS08 · M10 · HS08 · CW10 · OQ45	172

Figures as printed on this family's datasheet. A dash means the datasheet does not state that figure.