



SIERUTA

KS mini - cable bucket for mini-excavator

Models and specifications

Model	Machine class [t]	Width [mm]	Height [mm]	Length [mm]	Capacity SAE [dm³]	Tip radius [mm]	Quick coupler brackets	Weight [kg]
KS-20	0.6-3.0	200	491	615	19	418	S30 · S40 · MS01 · MS03 · M02 · M03 · HS02 · HS03 · OQ40	20
KS-20	0.6-3.0	300	491	615	33	418	S30 · S40 · MS01 · MS03 · M02 · M03 · HS02 · HS03 · OQ40	27
KS-20	0.6-3.0	400	491	615	50	418	S30 · S40 · MS01 · MS03 · M02 · M03 · HS02 · HS03 · OQ40	34
KS-50	3.0-5.0	300	635	790	53	533	S40 · MS03 · M10 · HS03 · OQ40	48
KS-50	3.0-5.0	400	635	790	79	533	S40 · MS03 · M10 · HS03 · OQ40	57
KS-50	3.0-5.0	500	635	790	107	533	S40 · MS03 · M10 · HS03 · OQ40	65
KS-100	5.0-10	300	857	1075	101	717	S40/240 · S45 · MS08 · M10 · HS06 · HS08 · OQ45	90
KS-100	5.0-10	400	857	1075	147	717	S40/240 · S45 · MS08 · M10 · HS06 · HS08 · OQ45	105
KS-100	5.0-10	500	857	1075	196	717	S40/240 · S45 · MS08 · M10 · HS06 · HS08 · OQ45	120

Figures as printed on this family's datasheet. A dash means the datasheet does not state that figure.