



SIERUTA

KSV mini - Scandinavian profile cable V bucket for mini-excavator

Models and specifications

Model	Machine class [t]	Width [mm]	Height [mm]	Length [mm]	Capacity SAE [dm³]	Tip radius [mm]	Quick coupler brackets	Weight [kg]
KSV-20	0.6-3.0	100	477	706	17	567	S30 · S40 · MS01 · MS03 · M02 · M03 · HS02 · HS03 · OQ40	23
KSV-20	0.6-3.0	200	477	706	36	567	S30 · S40 · MS01 · MS03 · M02 · M03 · HS02 · HS03 · OQ40	31
KSV-20	0.6-3.0	300	477	706	57	567	S30 · S40 · MS01 · MS03 · M02 · M03 · HS02 · HS03 · OQ40	40
KSV-50	3.0-5.0	100	533	790	22	635	S40 · MS03 · M10 · HS03 · OQ40	34
KSV-50	3.0-5.0	200	533	790	48	635	S40 · MS03 · M10 · HS03 · OQ40	40
KSV-50	3.0-5.0	300	533	790	71	635	S40 · MS03 · M10 · HS03 · OQ40	35
KSV-100	5.0-10	200	728	1075	101	857	S40/240 · S45 · MS08 · M10 · HS06 · HS08 · OQ45	91
KSV-100	5.0-10	300	728	1075	149	857	S40/240 · S45 · MS08 · M10 · HS06 · HS08 · OQ45	107
KSV-100	5.0-10	400	728	1075	201	857	S40/240 · S45 · MS08 · M10 · HS06 · HS08 · OQ45	122

Figures as printed on this family's datasheet. A dash means the datasheet does not state that figure.