SIERUTA

LR mini - straight land rakes for mini-excavator

Models and specifications

Model	Machine class [t]	Width [mm]	Height [mm]	Length [mm]	Number of tines	B [mm]	Spacing [mm]	Tine thickness [mm]	Quick coupler brackets	Weight [kg]
LR-2	0.7–1.5	1,000	400	222	12	122	72	15	S30 · MS01 · M02 · HS02 · CW05 · Klac C	56
LR-2	0.7–1.5	1,200	400	222	14	122	75	15	S30 · MS01 · M02 · HS02 · CW05 · Klac C	66
LR-3	1.5–2.5	1,000	500	275	12	155	72	15	S40 · MS03 · M03 · HS02 · CW05 · OQ40 · Klac C	85
LR-3	1.5–2.5	1,200	500	275	14	155	75	15	S40 · MS03 · M03 · HS02 · CW05 · OQ40 · Klac C	100
LR-4	2.5–4.0	1,000	600	331	12	187	72	15	S40 · MS03 · M03 · HS03 · CW05 · OQ40 · Klac D	127
LR-4	2.5–4.0	1,200	600	331	14	187	75	15	S40 · MS03 · M03 · HS03 · CW05 · OQ40 · Klac D	150
LR-6	4.0–6.0	1,000	650	352	11	208	74	20	S40 · MS03 · M03 · HS06 · CW10 · OQ40 · Klac E	158
LR-6	4.0–6.0	1,200	650	352	13	208	75	20	S40 · MS03 · M03 · HS06 · CW10 · OQ40 · Klac E	187
LR-8	6.0–8.0	1,000	740	397	11	243	74	20	S40/240 · MS08 · M10 · HS06 · CW10 · OQ45 · Klac F	189
LR-8	6.0–8.0	1,400	740	397	15	243	75	20	S40/240 · MS08 · M10 · HS06 · CW10 · OQ45 · Klac F	259

Figures as printed on this family’s datasheet. A dash means the datasheet does not state that figure.

Model	Machine class [t]	Width [mm]	Height [mm]	Length [mm]	Number of tines	B [mm]	Spacing [mm]	Tine thickness [mm]	Quick coupler brackets	Weight [kg]
LR-10	8.0–10	1,000	800	429	11	261	74	20	S45 · S50 · MS08 · M10 · HS08 · CW10 · OQ45 · Klac F	219
LR-10	8.0–10	1,400	800	429	15	261	75	20	S45 · S50 · MS08 · M10 · HS08 · CW10 · OQ45 · Klac F	300

Figures as printed on this family’s datasheet. A dash means the datasheet does not state that figure.