SIERUTA

SB mini - Dutch profile grading & ditching bucket for mini-excavator

Models and specifications

Model	Machine class [t]	Width [mm]	Height [mm]	Length [mm]	Heaped capacity ISO 7451 [dm³]	Tip radius [mm]	Quick coupler brackets	Weight [kg]
SB-10	0.6–1.2	600	280	337	35	328	CW00	27
SB-10	0.6–1.2	700	280	337	41	328	CW00	31
SB-10	0.6–1.2	800	280	337	47	328	CW00	35
SB-20	1.2–1.8	800	350	420	77	410	CW05	43
SB-20	1.2–1.8	900	350	420	89	410	CW05	48
SB-20	1.2–1.8	1,000	350	420	99	410	CW05	53
SB-30	1.8–2.5	900	393	472	97	454	CW05	65
SB-30	1.8–2.5	1,000	393	472	107	454	CW05	72
SB-30	1.8–2.5	1,100	393	472	119	454	CW05	78
SB-30	1.8–2.5	1,200	393	472	131	454	CW05	85
SB-40	2.5–4.0	1,000	445	534	149	520	CW05	93
SB-40	2.5–4.0	1,100	445	534	166	520	CW05	101
SB-40	2.5–4.0	1,200	445	534	184	520	CW05	109
SB-60	4.0–6.0	1,000	505	604	192	600	CW10	105
SB-60	4.0–6.0	1,100	505	604	215	600	CW10	115
SB-60	4.0–6.0	1,200	505	604	238	600	CW10	124
SB-60	4.0–6.0	1,300	505	604	261	600	CW10	134
SB-60	4.0–6.0	1,400	505	604	284	600	CW10	143
SB-75	6.0–7.5	1,200	560	666	283	665	CW10	164
SB-75	6.0–7.5	1,300	560	666	311	665	CW10	177
SB-75	6.0–7.5	1,400	560	666	341	665	CW10	189
SB-75	6.0–7.5	1,500	560	666	368	665	CW10	202
SB-75	6.0–7.5	1,600	560	666	396	665	CW10	214
SB-90	7.5–10	1,400	648	776	460	768	CW10	231
SB-90	7.5–10	1,500	648	776	498	768	CW10	246

Figures as printed on this family’s datasheet. A dash means the datasheet does not state that figure.

Model	Machine class [t]	Width [mm]	Height [mm]	Length [mm]	Heaped capacity ISO 7451 [dm³]	Tip radius [mm]	Quick coupler brackets	Weight [kg]
SB-90	7.5–10	1,600	648	776	537	768	CW10	261
SB-90	7.5–10	1,700	648	776	575	768	CW10	276
SB-90	7.5–10	1,800	648	776	614	768	CW10	291

Figures as printed on this family’s datasheet. A dash means the datasheet does not state that figure.