



SIERUTA

SDB - cazo de rejilla DB, reforzado

Modelos y especificaciones

Modelo	Clase de máquina [t]	Anchura [mm]	Altura [mm]	Longitud [mm]	Capacidad SAE [dm³]	Radio de punta [mm]	Sistemas de dientes	Enganches para enganche rápido	Peso [kg]
SDB-120	10-12	1000	866	925	435	785	J250, V19, U20	CW20 · SW33	286
SDB-120	10-12	1200	866	925	548	785	J250, V19, U20	CW20 · SW33	333
SDB-160	12-16	1000	978	1046	543	886	J300, V29, U30	CW20 · SW33	392
SDB-160	12-16	1200	978	1046	687	886	J300, V29, U30	CW20 · SW33	448
SDB-230	16-24	1400	1130	1296	1183	1071	J300, V29, U30	CW30 · SW33 · SW48	833
SDB-230	16-24	1500	1130	1296	1290	1071	J300, V29, U30	CW30 · SW33 · SW48	880
SDB-300	24-30	1500	1234	1318	1375	1121	J350, V33, U35	CW30 · CW40 · SW48	1051
SDB-300	24-30	1600	1234	1318	1492	1121	J350, V33, U35	CW30 · CW40 · SW48	1106
SDB-400	30-40	1600	1427	1511	1917	1283	J350, V33, U35	CW45 · SW48 · SW66	1411
SDB-400	30-40	1800	1427	1511	2224	1283	J350, V33, U35	CW45 · SW48 · SW66	1550
SDB-500	40-50	1800	1578	1678	2622	1431	J400, V39, U40	CW55 · SW66	1995
SDB-500	40-50	2000	1578	1678	3000	1431	J400, V39, U40	CW55 · SW66	2172

Datos tal como figuran en la ficha técnica de esta familia. Un guion indica que la ficha técnica no recoge ese dato.